

Part Number	32C0402
Print Technology	Color Laser
Function	Color Copying Color Faxing Color Printing Color Scanning Color Network Scanning
Workgroup Size	Large Workgroup
Touch Screen Display	Yes
Display	Lexmark e-Task 10-inch (25 cm) class color touch screen
Print Speed (Letter, Black)	Up to 55 ppm ⁶
Print Speed (Letter, Color)	Up to 55 ppm ⁶
Print Speed (Letter, Black) Duplex	Up to 55 spm ⁶
Time to First Page (Black)	As fast as 5.2 seconds
Time to First Page (Color)	As fast as 6.1 seconds
Duplex (2-sided) Printing	Integrated Duplex
Print Resolution, Black	1200 x 1200 dpi 2400 Image Quality
Print Resolution, Color	1200 x 1200 dpi 2400 Image Quality
Copy Speed (Letter, Black)	Up to 55 cpm ⁶
Copy Speed (Letter, Color)	Up to 55 cpm ⁶
Time to First Copy (Black)	As fast as 4.9 seconds
Time to First Copy (Color)	As fast as 5.8 seconds
Reduce / Enlarge Range	25 - 400 %
A4/Ltr Simplex Scan Speed (Black)	Up to 80 / 80 sides per minute
A4/Ltr Simplex Scan Speed (Color)	Up to 80 / 80 sides per minute
A4/Ltr Duplex Scan Speed (Black)	Up to 160 / 160 sides per minute
A4/Ltr Duplex Scan Speed (Color)	Up to 160 / 160 sides per minute
Scan Area, Maximum	11.69 x 17.0 inches
ADF Scan	DADF (single pass Duplex)
Scanner Type	Flatbed scanner with ADF
Scan Technology	CCD
Optical Scanning Resolution	600 X 600 ppi
Scan File Formats (Send as)	JPEG, JPG PDF Secure PDF TIFF XPS Archival PDF (A-1a, A-1b) Highly compressed PDF (1GB RAM and hard disk required) Searchable PDF
Scan Destinations	e-mail FTP USB Flash drive USB or Network connected computer Lexmark Document Solutions Suite (LDSS)
Modem Speed	ITU T.30, V.34 Half-Duplex, 33.6 Kbps
Fax Transmission Speed	< 3 seconds per page
Processor Speed	Quad Core 1.2 GHz
Memory, Standard	2048 MB
Memory, Maximum	4096 MB

Hard Disk	Included in configuration
Apple Operating Systems Supported	Apple OS X (10.6, 10.7, 10.8, 10.9, 10.10, 10.11)
Citrix MetaFrame	Microsoft Windows Server 2008 and 2008 X64 Edition with Citrix XenApp 5.0 Microsoft Windows Server 2008 R2 with Citrix XenApp 6.0, 6.5 Microsoft Windows Server 2012 with Citrix XenApp 6.0, 6.5
Linux Operating Systems Supported	Debian GNU/Linux 7.0, 8.0 Fedora 21, 22 Linpus Linux Lite Desktop 2.1 Linux Mint 13 LTS, 17 LTS, 17.1 LTS, 17.2 LTS Linux Mint 2 Debian PCLinuxOS 2014.12 Red Hat Enterprise Linux WS 4, 5, 6, 7 SUSE Linux Enterprise Desktop 10, 11, 12 SUSE Linux Enterprise Server 10, 11, 12 Ubuntu 12.04 LTS, 14.04 LTS, 15.04 openSUSE 13.1, 13.2 openSUSE Tumbleweed
Microsoft Windows Operating Systems Supported	Windows XP Windows XP x64 Windows Vista Windows Vista x64 Windows Server 2008 Windows Server 2008 x64 Windows 7 Windows 7 x64 Windows Server 2008 R2 Windows 8 Windows 8 x64 Windows Server 2012 Windows 8.1 Windows 8.1 x64 Windows Server 2012 R2 Windows RT Windows RT 8.1 Windows 10
Novell Operating Systems Supported	Novell NetWare 6.5 Open Enterprise Server Novell Open Enterprise Server on SuSE Linux Enterprise Server 10 SP4 (x86 and x64) Novell Open Enterprise Server on SuSE Linux Enterprise Server 11 SP4 (x86 and x64) Novell Open Enterprise Server on SuSE Linux Enterprise Server 12 SP1 (x86 and x64)

UNIX Operating Systems Supported	Sun Solaris x86 10, 11 IBM AIX 5.3, 6.1, 7.1 Sun Solaris SPARC 10, 11
Included Paper Handling	Integrated Duplex 250-Sheet Output Bin 150-Sheet Multipurpose Feeder 2 x 500-Sheet Input
Optional Paper Handling	Staple Finisher Staple Punch Finisher 2500-Sheet Tandem Tray 3000-Sheet Tray Booklet Finisher 2 x 500-Sheet Tray

Paper Input Capacity, Standard	Up to 1150 pages 20 lb or 75 gsm bond
Paper Input Capacity, Maximum	Up to 6650 pages 20 lb or 75 gsm bond
Paper Output Capacity, Standard	Up to 250 pages 20 lb or 75 gsm bond

Paper Output Capacity, Maximum	Up to 3500 pages 20 lb or 75 gsm bond
Paper Weight Range Supported - Standard Tray (lb.)	16 - 47 lb.
Paper Weight Range Supported - Multipurpose Feeder (lb.)	16 - 47 lb.

A3 / 11 x 17	Yes
ADF	100-Sheet Automatic Document Feeder

ADF Paper Input Capacity	Up to 100 pages 20 lb or 75 gsm bond
ADF Paper Output Capacity	Up to 100 pages 20 lb or 75 gsm bond

Finishing Option	Yes
Finishing Functions	Offset stacking Stapling Hole punching Booklet fold and saddle stapling

Number of Paper Inputs, Standard	3
Number of Paper Inputs, Maximum	6

Media Types Supported	Card Stock Envelopes Labels Plain Paper Refer to the Card Stock & Label Guide. Banner Paper
------------------------------	--

Media Sizes Supported	10 Envelope 7 3/4 Envelope 9 Envelope A3 A4 A5 B5 Envelope C5 Envelope DL Envelope Executive Folio JIS-B5 Legal Letter Statement Universal Super Tabloid (12 x 18") Oficio A6 SRA3
------------------------------	---

Standard Ports	One Internal Card Slot USB 2.0 Specification Hi-Speed Certified (Type B) Gigabit Ethernet (10/100/1000) Two Rear USB 2.0 Specification Hi-Speed Certified ports (Type A) Two Front USB 2.0 Specification Hi-Speed Certified port (Type A)
-----------------------	---

Optional Local Ports	External RS-232C serial Internal 1284-B Bidirectional Parallel
-----------------------------	---

Optional Network Ports	Internal MarkNet N8360 802.11b/g/n Wireless, NFC MarkNet N8230 Fiber Ethernet Print Server
-------------------------------	---

Direct USB	Yes
Ethernet Network	Yes

Wireless	Wireless Option
Network Protocol Support	TCP/IP IPv4 TCP/IP IPv6 TCP UDP

Network Printing Methods	LPR/LPD Direct IP (Port 9100) Enhanced IP (Port 9400) Secure IP (Port 96xx) FTP, TFTP ThinPrint .print integration Telnet IPP 1.0, 1.1, 2.0 (Internet Printing Protocol) Microsoft Web Services WSD Pull Printing
---------------------------------	--

Network Management Protocols¹	HTTP HTTPs (SSL/TLS) SNMPv1, SNMPv2c SNMPv3 WINS IGMP BOOTP, RARP APIPA (AutoIP) DHCP ICMP DNS Bonjour DDNS mDNS ARP NTP Telnet Finger
---	---

Network Security	SNMPv3 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS IPSec
-------------------------	--

Printable Area	0.165, 0.118, 0.118, 0.118 inches of the top, bottom, right and left edges (within)
Printer Languages (Standard)	PCL 5c Emulation PCL 6 Emulation Personal Printer Data Stream (PPDS) PostScript 3 Emulation Direct Image Microsoft XPS (XML Paper Specification) AirPrint™ PDF 1.7 emulation

Fonts and Symbol Sets	3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide 2 PCL bitmap fonts 39 scalable PPDS fonts 84 scalable PCL fonts OCR-A, OCR-B scalable PCL 5e fonts For more information, refer to the Technical Reference. 165 scalable PostScript fonts 15 PPDS bitmap fonts
------------------------------	---

Laser Cartridge Yields (up to)⁵	30,000-page Black and Colour (CMYK) Cartridges
---	--

Photoconductor Estimated Yield	Up to 100000 Black / 90000 (CMY) pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage ⁴
---------------------------------------	--

Cartridge(s) Shipping with Product	18,500-page Black Toner Cartridge 11,500-page Colour (CMY) Toner Cartridges
---	--

Replacement Cartridges:	Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details.
--------------------------------	--

Packaged Size (in. - H x W x D)	49.1 x 29.8 x 35.9 in.
--	------------------------

Packaged Weight (lb.)	293 lb.
------------------------------	---------

Size (in. - H x W x D)	36.3 x 24.2 x 27.4 in.
-------------------------------	------------------------

Weight (lb.)	239.2 lb.
---------------------	-----------

Size, Trays Extended (in. - H x W x D)	51.44 x 37.5 x 49.07 in.
---	--------------------------

Noise Level, Idle	29 dBA
--------------------------	--------

Noise Level (Print), Operating	52 dBA
---------------------------------------	--------

Duplex Print Noise Level, Operating	54 dBA
--	--------

Noise Level (Copy), Operating	56 dBA
--------------------------------------	--------

Noise Level (Scan), Operating	53 dBA
--------------------------------------	--------

ENERGY STAR	Yes
--------------------	-----

Average Power (Hibernate Mode)	0.2 watts
---------------------------------------	-----------

Average Power (Sleep Mode)	2.9 watts
-----------------------------------	-----------

Average Power (Ready Mode)	230 watts
-----------------------------------	-----------

Average Power (Printing)	1075 watts
---------------------------------	------------

Average Power (Copying)	1100 watts
--------------------------------	------------

Average Power (Scanning)	250 watts
---------------------------------	-----------

ENERGY STAR Typical Electricity Consumption (TEC)	4.6 kilowatt-hours per week
--	-----------------------------

Limited Warranty - See Statement of Limited Warranty	1-Year Onsite Service, Next Business Day
---	--

Product Certifications	ENERGY STAR, ICES-003 Class A, BSMI Class A, VCCI Class A, FCC Class A, NOM-032, UL, cUL, NOM, US FDA/CDRH, IEC 60825-1, CB Report, ISO-532B, CE (EU) DoC, EFTA (CE), KC logo, CCC, C-tick DoC, EuP, CECp, CEL, EC 1275/2008, ECMA-370, TED, SII, TER, SABS, UL-AR, GS Mark, Green Dot, ISO-9296, COC, CCD-035 EcoLogo, Green Mark, EPEAT, Blue Angel (Blauer Engel)
-------------------------------	--

Maximum Monthly Duty Cycle	Up to 250000 pages per month ³
-----------------------------------	---

Recommended Monthly Page Volume	7000 - 50000 pages ²
--	---------------------------------

Specified Operating Environment	Altitude: 0 - 2500 Meters (8,200 Feet) Humidity: 15 to 85% Relative Humidity Temperature: 10 to 30°C (50 to 86°F)
--	---

License/Agreement Terms	Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/printerlicense for details.
--------------------------------	--

Country of Origin	China (PRC)
--------------------------	-------------

UNSPSC Code
43212110

Harmonized Tariff Code
8443.31.0000

Developer Unit(s) Estimated Yield

Up to 600000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage

¹This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (<http://www.openssl.org/>)

²"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

³"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.

⁴Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity.

⁵Average yield at approximately 5% print coverage per colour.

⁶Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.